

Minimum System Requirements

- * 8" telescope
 - * ~1m effective focal length
 - * Equatorial mount or derotator
 - * Tracking at lunar rate
- * Astronomical video camera with adapter to fit telescope
 - * NTSC or PAL
 - * 1/2" detector
- * Digitizer - for digitizing video and creating a 720x480 .avi
 - * Segment .avi to files less than 1GB (8000 frames)
- * Time encoder/signal
 - * GPS timestamp or WWV audio
- * PC compatible computer
 - * ~80GB free disk space
- * Software for detecting flashes

System Example

- * 14" (355mm) f/8 Meade RCX400 on an equatorial wedge [or a 10" f/4.7 Newtonian]
- * 0.33x focal reducer [not used with the 10" f/4.7 Newtonian]
- * C-mount 1 1/4" adapter and baffle
- * ASTROVID StellaCam-EX (Sony HAD/EX chip)
- * SONY Video Walkman, GV-D800 NTSC, used as a FireWire digitizer
- * KIWI-OSD GPS time encoder
- * ICOM R8500 receiver
- * HP 2GHz Intel P4 with 1GB RAM
 - * 480GB, 7200rpm SATA hard drive
 - * FireWire card
- * Software
 - * Windows XP
 - * WinDV, used for recording and segmenting an .avi; vid+auds setting, segmented to 8000 frames
 - * LunarScan, used to locate impact flash candidates in an .avi
 - * VirtualDub, used for making flash and stellar calibration video clips
 - * Virtual Moon Atlas, used to locate the position of the flash on the moon

